



FUEL CONTAINER TYPE MT 450-1000



Mobile diesel and fuel oil supply for building site vehicles, machinery, equipment. For the international transport of hazardous liquids according to ADR/RID/IMDG codes, packing groups II and III

- outer container serves as a retention basin with 100 % retention volume including dipstick to register leakage
- inner tank (screwed to outer container) i.e. can be renewed, with opening for cleaning
- lockable spring supported lid, 100 mm ground leeway
- swivel crane eyes for crane handling and securing loads
- approved for diesel or heating fuel
- 2" threaded coupling with cap, 1" pump coupling with stop-cock
- pressure relief valve and airing valve
- Mark of Compliance ("Ü") Buildings Standards List A, "DIBt"
- UN-APPROVAL: 31 A/Y/D/BAUER/7336

Accessories

- manual pump
- electric pumps 12 V / 24 V / 230 V
- manual or electric flow counter
- level indicator
- marginal level
- safety valve
- loading traverse



Type	Volume in l	Dimensions (l x w x h) in mm	Floor area (l x w) in mm	Total permitted weight in kg	Weight (empty) without pump in kg
MT 450	450	1060 x 880 x 890	1000 x 800	775	239
MT 600	600	1360 x 880 x 890	1300 x 800	990	280
MT 1000	1000	1660 x 880 x 1100	1600 x 800	1557	356

FUEL CONTAINER TYPE MT-E 300-430



Mobile and single-walled tank for diesel and fuel oil supply for building site vehicles, machinery, equipment. For the transport with immediate use according to ADR 1.1.3.1 c

- sturdy welded construction
- lockable spring supported lid
- 100 mm ground leeway
- swivel crane eyes for crane handling and securing loads
- 2" threaded coupling with cap
- pressure relief valve and airing valve
- 1" pump coupling with stop-cock
- with pump changeable from 12V to 24V, with automatic nozzle and hose 4,0 m

Accessories

- manual or electric flow counter
- level indicator

Type	Volume in l	Dimensions (l x w x h) in mm	Floor area (l x w) in mm	Total permitted weight in kg	Weight (empty) without pump in kg
MT-E 300	300	1060 x 877 x 888	1000 x 800	535	171
MT-E 430	430	1060 x 877 x 888	1000 x 800	685	171

Finish:

hot-dip galvanized



MINI-TANK TYPE MT 235



Suitable for filling building site vehicles and machinery, equipment etc.

For the international transport of hazardous liquids according to ADR/RID/IMDG codes, packing groups II and III.

For the storage of flammable liquids carrying the symbols F / F+

- outer container (including frame) serves as a retention basin with 100 % retention volume
- inner tank (screwed to outer container) with stacking frame, manhole cover and fittings dipstick to register any leakage
- 2" coupling for pump
- filling coupling with threaded connection
- aeration valve
- can be locked
- can be stacked
- suitable for pick-up by pallet-, forklift truck or crane
- for indoor and outdoor use
- Mark of Compliance ("Ü") Buildings Standards List A, "DIBt"
- UN-APPROVAL: 31 A/Y/D/BAUER/031

Accessories

- manual pump
- level indicator

Type	Volume in l	Dimensions (l x w x h) in mm	Total permitted weight in kg	Weight in kg
MT 235	235	800 x 800 x 1248	725	220

Finish: **hot-dip galvanized**

Request

Please send the completed request form by fax, e-mail or call us.

We ask for an offer for the following products

Type	No. of

Please send us the BAUER-catalogue 5.0

Please contact us

.....
company

.....
contact person

.....
street, postcode

.....
town, country

.....
telephone, fax

.....
e-mail

.....
date/signature

... made by



Bauer GmbH

Eichendorffstr. 62 · 46354 Südlohn/Germany
 Tel. + 49 2862 709-0 · Fax +49 2862 709-155
 E-Mail: info@bauer-suedlohn.de
 Website: www.bauer-suedlohn.com
 Website: www.geotainer.com