

WHEELIE BIN JACK TYPE MH



Type MH-III

Type MH-II with 1100 litres wheelie bin

| Type | max. no. of (80-360 l wheelie bins) | max. no. of (1100 l wheelie bin) | Dimensions (lxwxh) in mm | Load capacity in kg | Weight painted approx. in kg |
|--------|--|-------------------------------------|-----------------------------|------------------------|---------------------------------|
| MH-I | 1 | - | 1026 x 584 x 678 | 200 | 65 |
| MH-II | 2 | 1 | 1026 x 1070 x 678 | 400 | 71 |
| MH-III | 3 | - | 1026 x 1595 x 678 | 600 | 79 |

A safe and efficient way to transport wheelie bins

- sturdy frame with fork sleeves
- rubber guard(s) to prevent damage to wheelie bin(s)
- gripping mechanism screwed to frame
- available for 1 up to 3 wheelie bins
- can be secured to prevent slipping

Design


Type MH-I / Type MH-III

- Manufactured to DIN EN 840-1, for wheelie bins ranging from 80 to 360 litres made of plastic and 240 litres wheelie bins made of steel sheeting

Type MH-II

- For 1100 litres wheelie bins with compick-up-system

Fork sleeve inside dimensions in mm



| Type | A | B | C |
|---------------|-----|-----|----|
| MH-I - MH-III | 230 | 170 | 75 |

WHEELIE BIN TIPPING STATION TYPE MKS



Type MKS-F

| Type | Dimensions (lxwxh) in mm | Load capacity in kg | Weight painted approx. in kg |
|----------|-----------------------------|------------------------|---------------------------------|
| MKS-F | 1200 x 950 x 1730 (3061) | 110 | 100 |
| MKS-H | 1200 x 950 x 1730 (3061) | 110 | 100 |
| MKS-12V | 1200 x 950 x 1730 (3061) | 110 | 115 |
| MKS-230V | 1200 x 950 x 1730 (3061) | 110 | 115 |



For emptying and cleaning of 120-/240-liter bins

- hydraulic or electric construction
- approx. 39 strokes required for hydraulic construction
- tilting angle up to 130°
- emptying height approx. 1480 mm
- 2 swivel + 2 fixed polyamide castors Ø 180 mm, one swivel castor with brake - construction height 220 mm

Design

Type MKS-F

- with foot pump

Type MKS-H

- with hand pump

Type MKS-12V

- electric-hydraulic 12 V (without charger)

Type MKS-230V

- electric-hydraulic 230 V

Accessory

- external charger for electric-hydraulic construction 12 V

Finish:

RAL 2000

RAL 3000

RAL 5012

RAL 6011

RAL 7005

hot-dip galvanized