

# SWARF BARROW TIPPER TYPE SKW



**Specially designed to collect metal shavings, is emptied at ground level**

- perforated base sieve, perforation  $\varnothing$  3 mm, separation 6 mm and 1" drain-cock
- sturdy steel sheeting construction with reinforced edging
- welding, oil- and watertight
- spring-retention avoids unintentional emptying, handle
- 2 wheels + 1 swivel castor (as of Type SKW 600 upwards + 2 swivel castors) made of solid rubber  $\varnothing$  250 x 60 mm, one swivel castor with brake

## Accessories

- fork sleeves (abbr. "FS") can be secured to prevent slipping and unintentional emptying
- galvanized lid, can be opened from both sides

Type	Volume (approx.) in l	Dimensions in mm (l x w x h)	Height dumping edge in mm	Load capacity in kg	Weight painted in kg without FS	Weight painted in kg with FS
SKW 250	250	1120 x 820 x 990	690	300	74	85
SKW 400	400	1330 x 900 x 1090	740	300	89	101
SKW 600	600	1400 x 1070 x 1220	830	300	133	145
SKW 1000	1000	1430 x 1340 x 1285	870	300	161	173

**Fork sleeve inside dimensions in mm**

Other dimensions possible

Type	A	B	C
SKW 250-1000	465	170	55

# SWARF DUMPER SKIP



**Low construction height makes this unit particularly well-suited for low-level swarf discharge**

- perforated sieve and 1" drain-cock designed to separate liquids from solids and drain them
- tiltable skip with handle
- sturdy frame with fork sleeves
- welding, oil- and watertight
- can be secured to prevent slipping and unintentional emptying

## Accessories

- 2 swivel + 2 fixed solid rubber castors  $\varnothing$  200 x 50 mm, 1 swivel castor with brake - construction height 235 mm.

**Fork sleeve inside dimensions in mm**

Type	A	B	C
SKK 250	205	170	55
SKK 400	285	170	55
SKK 600	455	170	55
SKK 800	525	170	55
SKK 1000	725	170	55
SKN 250	285	170	55
SKN 400	455	170	55

Type	Volume (approx.) in l	Dimensions in mm (l x w x h)	Height dumping edge in mm	Load capacity in kg	Weight painted in kg
SKK 250	0.25	1130 x 590 x 740	440	300	70
SKK 400	0.40	1320 x 670 x 840	490	300	77
SKK 600	0.60	1390 x 840 x 910	520	300	125
SKK 800	0.80	1420 x 910 x 980	560	300	133
SKK 1000	1.00	1420 x 1110 x 980	560	300	145
SKN 250	0.25	1320 x 670 x 535	535	300	70
SKN 400	0.40	1390 x 840 x 610	610	300	77

Finish:

RAL 2000

RAL 3000

RAL 5012

RAL 6011

RAL 7005

hot-dip galvanized