FUEL CONTAINERS TYPE MT 450-1000



MT 450 with electric pump



MT 1000 with electric pump



- (1) lid
- (2) filling coupling
- (3) ball valve
- (4) level indicator
- (5) ball valve/suction pipe
- (6) pump nozzle
- (7) bracket

Mobile diesel and fuel oil supply for building site vehicles, machinery, equipment. For the international transport of hazardous liquids according to ADR/RID and the IMDG code, packing groups II and III

- outer container provides 100% spill containment including dipstick to register leakage
- inner tank (screwed to outer container) i.e. can be renewed, with opening for cleaning
- lockable spring-loaded lid
- 100 mm ground leeway
- swivel crane eyes for crane handling and securing loads
- 2" threaded coupling with cap, 1" pump coupling with stopcock
- pressure relief valve and airation valve
- no haz mats licence required for Germany check YOUR stipulations!

Accessories

- manual pump
- electric pumps 12 V / 24 V / 230 V
- manual or electric flow counter
- level indicator
- loading traverse

	Volume in I	Dimensions (I x w x h) in mm	Floor area (I x w) in mm	Total permitted weight in kg	Weight empty without pump in kg
MT 450	450	1060 x 880 x 890	1000 x 800	775	239
MT 600	600	1360 x 880 x 890	1300 x 800	990	280
MT 1000	1000	1660 x 880 x 1100	1600 x 800	1557	356

UN- <i>A</i>	۱PP	RO'	VA	LS
--------------	-----	-----	----	----

31A/Y/D/BAM 7336-BAUER/0/