LIFTOMAT TYPE L

L/E 1300 in action with sump tray type S 2018 (see page 94)

Controlled emptying of steel bunghole drums, steel drums with a lid, steel rolling hoop drums, plastic L-ring drums, plastic double L-ring drums and plastic drums with a lid ranging from 110 to 220 litres

- range of rotation up to 270°
- 2 swivel castors Ø 175 mm and 2 fixed castors Ø 200 mm made of solid rubber, both swivel castors with brake
- safe pick-up guaranteed; drum is held by the tension band at the front and spindle at the top
- with crank handle and self-braking gear box

Types available

L/E

- electro-hydraulic construction fitted with maintenance-free battery 12V/88Ah and charger for 230 V mains connection

L/M

- hydraulic construction with manual pump

Individual construction on request

L/E 1300

L/M 1300

L/M 1300 "ex"-zone construction (individual construction)

	Design	Dimensions (l x w x h) in mm	Load capacity in kg	Stroke height in mm	Lift height in mm	Emptying height in mm	Range of rotation in degree	Weight paint. / galv. in kg
L/M 600	hydraulic	1390 x 1120 x 1230	350	18	450	600	270	156 / 168
L/M 1300	hydraulic	1390 x 1120 x 1915	350	18	1100	1300	270	192 / 210
L/E 1300	electro-hydraulic	1390 x 1120 x 1915	350	--	1100	1300	270	220 / 238

Finish: RAL 2000 | RAL 5012 | hot-dip galvanized