

# SPECIAL WASTE CONTAINER TYPE SAP



SAP 800

**For the international transport of solids and paste-like substances according to ADR/RID and the IMDG code, packing groups I, II and III**

- IBC according to DIN standard 30741, part 1
- construction made of 3 mm steel sheet, lid and base frame 2.5 mm steel sheet
- reinforced edging
- full-length fork sleeves
- sturdy stacking corners with crane lifting eyes
- suitable for pick-up by a pallet truck, forklift or crane
- 4 lid fasteners, lockable
- spring-loaded lid with a seal
- automatic lid lock in 270° position
- lid support in 70° position
- max. density 1.5 kg/l
- finish hot-dip galvanized or with additional painted finish (outside only)

### Accessories

- PE foil bags (50 bags/roll)
  - PE inlay
  - embossed company name
  - dual code
- NB Please remember to check whether this option is regulation compliant for you! (A dual code is permitted in Germany)

### Individual construction on request e.g.

- stainless steel



SAP 800 with PE inlay (please see Accessories)



PE foil bags on a roll (please see Accessories)

**§ UN-APPROVALS**

UN 11A/X/D/BAM 0410-BAUER/5148/  
UN 4A/X/S/D/BAM 10012-BAUER

	Volume in l	Dimensions in mm (l x w x h)	Can be stacked	Total permitted weight in kg	Weight in kg
SAP 450	450	1200 x 1000 x 835	3 high	868	185
SAP 600	640	1200 x 1000 x 1053	3 high	1175	200
SAP 800	800	1200 x 1000 x 1235	3 high	1430	215

Finish: **hot-dip galvanized**