

SPECIAL WASTE CONTAINERS TYPE SAP



SAP 800

For the international transport of solids and paste-like substances according to ADR/RID and the IMDG code, packing groups I, II and III

- IBC according to DIN standard 30741, part 1
- dual code
- construction made of 3 mm steel sheet, lid and base frame 2.5 mm steel sheet
- reinforced edging
- full-length fork sleeves
- sturdy stacking corners with crane lifting eyes
- suitable for pick-up by a pallet truck, forklift or crane
- 4 lid fasteners, lockable
- spring-loaded lid with a seal
- automatic lid lock in 270° position
- lid support in 70° position
- max. density 1.5 kg/l

Accessories

- PE foil bags black (50 bags/roll)
- PE inlay
- embossed company name



SAP 800 with PE inlay (please see Accessories)



PE foil bags on a roll (please see Accessories)

UN-APPROVALS

- Ⓡ 11A/X/D/BAM 0410-BAUER/5148/
- Ⓡ 4A/X/S/D/BAM 10012-BAUER

	Volume in l	Dimensions (l x w x h) in mm	Can be stacked	Total permitted weight in kg	Weight in kg
SAP 450	450	1200 x 1000 x 835	3 high	868	185
SAP 600	640	1200 x 1000 x 1050	3 high	1175	200
SAP 800	800	1200 x 1000 x 1235	3 high	1415	215

Finish:

hot-dip galvanized