

# TIPPING SKIPS TYPE KK / SKK



## Ideal for collection and disposal of bulk solids and industrial waste

- sturdy steel sheet construction with reinforced edging
- tiltable skip with handle
- sturdy frame with fork sleeves
- easy to transport using a forklift truck
- welding, oil and watertight
- can be secured to prevent slipping and unintentional emptying
- wheels can be fitted later

### Types available

#### Tipping Skip **KK**

- as above

#### Swarf Tipping Skip **SKK**

- with perforated sieve and 1" drain-cock designed to separate liquids from solids and drain them

KK



KK



KK with castors (solid rubber)



1" drain-cock



Perforated corner sieve

### Accessories

- 2 swivel + 2 fixed solid rubber castors Ø 200 mm, 1 swivel castor with brake  
– construction height 235 mm
- 2 swivel + 2 fixed polyamide castors Ø 180 mm, one swivel castor with brake  
– construction height 225 mm
- galvanized lid, can be opened from both sides



SKK



SKK with castors (solid rubber)

	Volume approx. in l	Dimensions (l x w x h) in mm	Height dumping edge in mm	Load capacity in kg	Weight in kg paint. / galv.
<b>KK 250</b>	250	1115 x 590 x 740	430	300	59 / 63
<b>KK 400</b>	400	1320 x 670 x 840	484	300	73 / 79
<b>KK 600</b>	600	1390 x 840 x 905	516	300	114 / 123
<b>KK 800</b>	800	1420 x 910 x 975	556	300	125 / 134
<b>KK 1000</b>	1000	1420 x 1110 x 975	556	300	138 / 148
<b>SKK 250</b>	250	1115 x 590 x 740	430	300	61 / 66
<b>SKK 400</b>	400	1320 x 670 x 840	484	300	75 / 81
<b>SKK 600</b>	600	1390 x 840 x 905	516	300	116 / 125
<b>SKK 800</b>	800	1420 x 910 x 975	556	300	127 / 137
<b>SKK 1000</b>	1000	1420 x 1110 x 975	556	300	140 / 151

Fork sleeve inside dimensions in mm			
	A	B	C
<b>KK / SKK 250</b>	205	170	55
<b>KK / SKK 400</b>	285	170	55
<b>KK / SKK 600</b>	455	170	55
<b>KK / SKK 800</b>	525	170	55
<b>KK / SKK 1000</b>	725	170	55