

# CONTAINERS WITH DROP AWAY BASE TYPE BKB



## Conical container, bottom discharge

- can be stacked inside one another
- trap door operated by cable from the driver's seat
- trap door closes automatically when the container is set down on the ground, opening angle 90°
- sturdy construction with all-round reinforced edging
- suitable for pick-up by a forklift or crane
- 100 mm ground leeway, suitable for pallet trucks
- can be secured to prevent slipping and unintentional trap door operation
- wheels can be fitted later

## Accessories

- 2 swivel + 2 fixed polyamide castors Ø 180 mm, one swivel castor with brake - construction height 225 mm
- galvanized lid, can be opened from both sides (stacking NOT possible)



BKB with lid



BKB with castors

**Fork sleeve (hoops) inside dimensions in mm**

	A	B	C
BKB 500-1000	600	180	65

**Fork sleeve inside dimensions in mm**

Type	A	B	C
BKB 500-1000	600	180	94

	Volume (approx.) in m <sup>3</sup>	Dimensions (l x w x h) in mm	Load capacity in kg	Weight in kg paint. / galv.
BKB 500	0,50	1040 x 1200 x 715	1000	126 / 136
BKB 700	0,70	1040 x 1200 x 970	1500	145 / 156
BKB 1000	1,00	1040 x 1200 x 1270	2000	169 / 182

Finish:

RAL 2000

RAL 3000

RAL 5012

RAL 6011

RAL 7005

hot-dip galvanized