

SWARF TILTING CONTAINERS TYPE SGU / SGU-RZ



SGU

Especially designed to separate liquids from solids and collect them

- 1" drain-cock to drain off liquids
- can be emptied at any height by cable operated from the driver's seat
- body with all-round reinforced edging
- sturdy frame with fork sleeves
- can be secured to prevent slipping and unintentional emptying
- welding, oil and watertight

Types available

Swarf Container SGU

- perforated intermediate screen screwed in 100 mm above the floor, perforation Ø 3 mm, separation 6 mm

Swarf Tilting Container for Tugger Train Systems SGU-RZ

- perforated intermediate screen, screwed in 50 mm above the floor, perforation Ø 3 mm, separation 6 mm, 1" drain-cock
- for trolley measuring 1200 x 800 mm

Accessories

- 2 swivel + 2 fixed polyamide castors Ø 180 mm, one swivel castor with brake – construction height 225 mm
- galvanized lid, can be opened from both sides
- pick-up for a crane, lever trolley or pallet truck
- trailer coupling and towing bar
- adjustable dumping brake (not for SGU 30)



SGU



SGU-RZ on a trolley



SGU with castors



Perforated intermediated sieve

Individual constructions on request



1" drain-cock

	Volume (approx.) in m ³	Dimensions (l x w x h) in mm	Load capacity in kg	Weight in kg paint. / galv.
SGU 30	0,30	1440 x 680 x 580	750	112 / 121
SGU 50	0,50	1440 x 780 x 680	1000	130 / 140
SGU 75	0,75	1440 x 1280 x 680	1000	169 / 182
SGU 100	1,00	1640 x 1280 x 780	1500	220 / 237
SGU 150	1,50	1640 x 1280 x 1090	1500	250 / 270
SGU 200	2,00	1640 x 1680 x 1090	1500	287 / 308
SGU-RZ 30	0,30	1230 x 875 x 530	750	123 / 131
SGU-RZ 55	0,55	1230 x 875 x 880	1000	143 / 153

	Fork sleeve inside dimensions in mm		
	A	B	C
SGU 300	10	200	60
SGU 500 / SGU-RZ 30-55	150	200	60
SGU 750-2000	495	200	60

Finish:	RAL 2000	RAL 3000	RAL 5012	RAL 6011	RAL 7005	hot-dip galvanized
---------	----------	----------	----------	----------	----------	--------------------