

FILLING POINTS



AW 60-3 + GR 60-3
+ 3xAG 60-3 + 9xFA 60-A



FA 60-A



RA 60-A


Horizontal storage and filling. For max. 9 x 60 litre drums/canisters or 60 litre drums/canisters in combination with small cans

Modular design, choose from:

- **Sump trays AW 60** made of 3 mm steel sheet, 100 mm ground leeway
- **Grids GR**, galvanized (load capacity 1000 kg/m²)
- **Canister Stands AG**, galvanized, in kit form, can be stacked max. 3 high
- **Drum Supports AB** (2 pieces per canister), galvanized, movable
- **Drum support FA 60-A** for 1 x 60 litre drum, galvanized
- **Clip-on Rotating Support RA 60-A**, galvanized, for rotating 60 litre drums



AW 60-3 + GR 60-3
+ 2xAG 60-3 + 12xAB



AB (2 pieces per canister)



AW 60-2 + 2xAG 60-2 + 4xFA 60-A



Tilting Canister Stand KAH 60 with Sump Tray AW 60-2/M

	Max. no. of 60 litre drums	Dimensions (l x w x h) in mm	Retention capacity in l	Load capacity in kg	Weight in kg paint. / galv.
Sump tray	AW 60-1	800 x 500 x 290	73	--	28 / 30
Grid	GR 60-1	780 x 420 x 30	--	--	-- / 6
Shelf	AG 60-1	515 x 515 x 555	--	65	-- / 9
Sump tray	AW 60-2	900 x 800 x 220	82	--	34 / 38
Grid	GR 60-2	820 x 780 x 30	--	--	-- / 12
Shelf	AG 60-2	915 x 515 x 555	--	130	-- / 10
Sump tray	AW 60-3	1300 x 800 x 205	103	--	42 / 48
Grid	GR 60-3	1220 x 780 x 30	--	--	-- / 18
Shelf	AG 60-3	1315 x 515 x 555	--	200	-- / 13
Canister Stand	AB	105 x 510 x 150	--	--	-- / 2
Drum Support	FA 60-A	270 x 510 x 60	--	--	-- / 2
Clip-on Rotating Support	RA 60-A	270 x 510 x 80	--	--	-- / 4

- every unit tested for leakage
- flammable liquids, GHS categories 1 - 3
- hazardous to aquatic environment, GHS categories 1 - 4