

MOBILE SUMP TRAYS WITH PERFORATED PANEL TYPE LPW



LPW 200-2 with tool deposit and drip tray

Dispense oils etc. from 60 or 200 litre drums, wherever necessary - mobile, safe, simple

- 3 mm steel sheet sump tray
- galvanized grid (load capacity 1000 kg/m²)
- sturdy rear panel, perforated, galvanized steel sheet with 10 x 10 mm square holes, straight row pattern, 38 mm spacing allows tool holders to be positioned as required
- hot-dip galvanized handles

LPW 200-1, -2, -3

- set of polyamide castors: 2 fixed and 2 swivel, (1 swivel castor with a brake) Ø 180 mm, construction height 225 mm

LPW 60-1, -2, -3

- set of polyamide castors: 2 fixed and 2 swivel, (1 swivel castor with a brake) Ø 100 mm, construction height 125 mm

LPW 200-4

- with perforated tool board
- assembly board on the sump tray
- with tension belt
- castors - Ø 100 mm - construction height 125 mm

Accessories

- galvanized tool deposit
- galvanized drip tray with fixture to hook up pump nozzle



	Max. no. of drums x litre	Dimensions in mm (l x w x h)	Dim. tray only in mm (l x w x h)	Retention capacity in l	Weight painted/ galv. in kg
LPW 60-1	1x 60	570 x 590 x 1775	500 x 500 x 505	67	52 / 54
LPW 60-2	2x 60	570 x 890 x 1685	500 x 800 x 415	73	64 / 66
LPW 60-3	2x 60	875 x 500 x 1685	800 x 500 x 415	73	56 / 58
LPW 200-1	1x 200	870 x 890 x 2110	800 x 800 x 610	222	100 / 104
LPW 200-2	2x 200	870 x 1290 x 2015	800 x 1200 x 515	243	122 / 126
LPW 200-3	2x 200	1280 x 800 x 2015	1200 x 800 x 515	243	110 / 114



- every unit tested for leakage
- flammable liquids, GHS categories 1 - 3
- hazardous to aquatic environment, GHS categories 1 - 4